

**FASSON® Crack-Back® Plus Coverall Art FSC® Certified**

Issued July 2025

**Introduction**

A self-adhesive paper sheet product for offset printing combined with the unique, diagonal Crack-Back Plus backing removal system.

**Description**

**Face:** An opaque premium-quality multi-coated woodfree paper, mirror-like finished glossy surface, white.  
 This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Availability	Adhesive 	Permanent
<i>Backing</i> 		
Crack-Back® Plus (diagonal cracklines)		<b>x</b>

**Printing & Conversion**

Offset printing.

Before applying the label, the surface must be clean, dry and grease-free.

**Features:** Excellent layflatness, enabling high-speed printing and good ink coverage level. The unique Crack-Back Plus backing removal system with diagonal scored lines facilitates creating lay-outs, conversion and application of the label. Product has excellent correction-, overposting- and block-out characteristics.

**Uses:** Correction-, cover-up-, overposting-, block-out- and packaging labels/stickers with a gloss finish: on flat or curved surfaces. Hospital labeling order picking-, shipping-, inventory labels: on flat or curved surfaces. For indoor use only.

**General**

Shelf life: 2 years stored at 20°C / 55% R.H.  
 Total caliper ( $\pm 10\%$ ): 164 micron

For information regarding EHS regulation, please visit our website under downloads “Technical bulletins“ TB 7.8 Product Compliance Fasson Offset” and for technical guidance “Technical bulletins“ – Offset printing.

# FASSON® Crack-Back® Plus Coverall Art FSC® Certified

## PRODUCT CHARACTERISTICS

### Physical properties

#### Face

Basis weight:	80 g/m <sup>2</sup>	ISO 536
Caliper:	65 micron	ISO 534

---

#### Adhesive

Permanent:	General-purpose water-based permanent adhesive with a high initial tack and high adhesion on most common substrates.
------------	--

#### Permanent

Adhesion (N/25mm) (FTM 1 on steel/20 min. bond time)	15.4
Tack (N) (FTM 9 on st.steel)	10.3
Minimum application temperature	+5
Service temperature range after 24 hrs (°C)	+80
Resistance to cold (°C) <sup>1)</sup> down to	-20

<sup>1)</sup> Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.

---

#### Backing

Crack-Back® Plus: One-side-coated bleached kraft paper, with diagonally crush-scored lines, along which the backing will crack cleanly when bent back, allowing easy removal in just two pieces. Lines are spaced just 32 mm apart. Good layflatness ensures first-class printing and finishing.

#### Remarks on Crack-Back® Plus

We advise not to use Crack-Back® Plus for labels larger than A5 (148.5 x 210 mm) or smaller than A8 (52 x 74 mm). For products not complying to these recommendations Torraspapel - Lecta does not take responsibility for the functionality of the score lines.

Basis weight:	86 g/m <sup>2</sup>	ISO 536
Caliper:	87 micron	ISO 534

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

---

#### Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All products are sold subject to Torraspapel - Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>

Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.