

PRODUCT DATA



FASSON® MC Matt DI-OFF FSC® Certified

Issued July 2025

Introduction

Qualified self-adhesive material for INDIGO DIGITAL presses. Optimized to secure excellent runability and print performance.

Description

Face: Premium-quality machine-coated woodfree paper, matt finish, white.
This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Availability

Adhesive ➡ Permanent

Backing U

Crack-Back® Plus (diagonal cracklines)	x
--	---

Printing & Conversion

This product is specifically engineered for use on the INDIGO DIGITAL sheet-fed press. The face material gives good toner key (no pre-treatment needed).
Stable construction ensures problem-free runability.
Before applying the label, the surface must be clean, dry and grease-free.
Also printable in conventional offset.

Features:

Qualified material ensures problem free conversion.
The unique Crack-Back® Plus: backing removal system with diagonal scored lines facilitates creating lay-outs, conversion and application of the label.

Recommendations for use

Multi-colour quality labels, promotional and collectable stickers using the advantages of full-colour DIGITAL printing such as: short runs, personalization etc.
For indoor use.

General

Shelf life: 2 years stored at 20°C / 55% R.H.
Total caliper (±10 %): 177 micron

For information regarding EHS regulation, please visit our website under downloads “Technical bulletins” TB 7.8 Product Compliance Fasson Offset” and for technical guidance “Technical bulletins” – Offset printing.

PRODUCT CHARACTERISTICS

Physical properties

Face

Basis weight:	90 g/m ²	ISO 536
Caliper:	79 micron	ISO 534
Opacity:	92 %	ISO 2471

Adhesive

Permanent: General-purpose water-based permanent adhesive with a high initial tack and high adhesion on most common substrates.

Permanent

Adhesion (N/25mm) (FTM 1 on steel/20 min. bond time)	15.4
Tack (N) (FTM 9 on st. steel)	10.3
Minimum application temperature	+5
Service temperature range after 24 hrs (°C)	+80
Resistance to cold (°C) ¹⁾ down to	-20

¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.

Backing

Crack-Back® Plus: One-side-coated bleached kraft paper, with diagonally crush-scored lines, along which the backing will crack cleanly when bent back, allowing easy removal in just two pieces. Lines are spaced just 32 mm apart. Good layflatness ensures first-class printing and finishing.

Remarks on Crack-Back® Plus

We advise not to use Crack-Back® Plus for labels larger than A5 (148.5 x 210 mm) or smaller than A8 (52 x 74 mm). For products not complying to these recommendations Torraspapel - Lecta does not take responsibility for the functionality of the score lines.

Basis weight:	86 g/m ²	ISO 536
Caliper:	87 micron	ISO 534

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
All products are sold subject to Torraspapel - Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>
Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.